

# UP0451E12P 45 W AC/DC Adapter

1  
Application  
Server  
Platform

2  
Single  
Board  
Computer

3  
IBX Series  
POS PC

4  
AFOLUX  
POS  
Panel PC

5  
Video  
Capture  
Card

6  
KAMIO  
RISC

7  
IOVU  
Open HMI

8  
VITO  
Universal  
Controller

9  
DINO  
BLADE

10  
LCD  
Product  
Series

11  
Embedded  
System

12  
Industrial  
Computer  
Chassis

13  
Power  
Supply

14  
Peripherals




## Specifications

- Input Voltage Range: 90-264 VAC
- Input Frequency: 47-63 Hz
- Output Voltage: 12 V
- Output Current: 3.75 A
- Output Watts: 45 W
- Efficiency: 75 %
- Operating Temperature: 0 °C ~ 40 °C
- Storage Temperature: -25 °C ~ 65 °C

## Ordering Information

Part No.	Description
63000-UP0451E12P71L-RS	12 V 45 W Power adapter with lock screw; 90~264 Vac input

## Dimensions



## Optional Cable



PN: CB-P1LP4-RS  
20 cm cable for 5.5X2.5 DC Plug with screw

## Connector Type



Plug Type:  $\phi$ in 2.5 mm /  $\phi$ out 5.5 mm

# UP0251E12PL 25 W AC/DC Adapter

7  
IOVU  
Open HMI

8  
VITO  
Universal  
Controller

9  
DINO  
BLADE

10  
LCD  
Product  
Series

11  
Embedded  
System

12  
Industrial  
Computer  
Chassis

13  
Power  
Supply

14  
Peripherals




## Specifications

- Input Voltage Range: 90-264 VAC
- Input Frequency: 47-63 Hz
- Output Voltage: 12 V
- Output Current: 2.1 A
- Output Watts: 25 W
- Efficiency: 85 %
- Operating Temperature: 0 °C ~ 50 °C
- Storage Temperature: -40 °C ~ 85 °C

## Ordering Information

Part No.	Description
63000-UP0251E12PL59-RS	12 V 25 W power adapter with lock screw; 90~264 Vac input

## Dimensions




## Optional Cable



PN: CB-P1LP4-RS  
20 cm cable for 5.5X2.5 DC Plug with screw

## Connector Type



Plug Type:  $\phi$ in 2.5 mm /  $\phi$ out 5.5 mm